

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015064 A1

(51) International Patent Classification⁷: F16J 15/34,
F16C 17/06

(GB). SARGENT, Raymond, Frederick [GB/GB]; 8
Stokefield Close, Thornbury, Bristol BS23 1HJ (GB).
CROSS, Edward, Henry [GB/GB]; Bladud, 54 Entry
Hill, Bath BA2 5LU (GB).

(21) International Application Number:
PCT/GB2004/003012

(74) Agents: DUNLOP, Brian, Kenneth, Charles et al.;
Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham GL50 1JJ (GB).

(22) International Filing Date: 12 July 2004 (12.07.2004)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/488,802 22 July 2003 (22.07.2003) US
0317055.2 22 July 2003 (22.07.2003) GB

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(71) Applicant (for all designated States except US): CROSS
MANUFACTURING COMPANY (1938) LIMITED
[GB/GB]; Midford Road, Bath, Avon BA2 5RR (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): CROSS, Rodney,
Alan [GB/GB]; 208a Old Frome Road, Bath BA2 5RH

[Continued on next page]

(54) Title: IMPROVEMENTS RELATING TO NON-CONTACTING FACE SEALS AND THRUST BEARINGS

(57) Abstract: The apparatus, which can be used in aspirating face seals or thrust bearings, spaces two relatively rotatable facing surfaces in use by entraining gas between the surfaces. The apparatus includes a first portion (1) defining a generally frusto-conical surface (3); a second portion (2) defining at least one flat surface disposed adjacent the first portion so that the two surfaces face each other and define at least one point of closest engagement between the surfaces, with diverging gaps extending between the surfaces on either side of a plane which contains the point or points of closest engagement and which extends generally orthogonal to the direction of relative rotation, and a device (4) for biasing the flat surface towards the frusto-conical surface to maintain the gaps within a predetermined dimensional range.





European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NU, SN, TD, TG).

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with International search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.